




O型環標準尺寸公制規格表

JIS B2401 P (公制單位 mm)



規格	內徑	外徑	厚度
P-002	1.8	5.6	1.9
P-003	2.8	6.6	1.9
P-004	3.8	7.6	1.9
P-005	4.8	8.6	1.9
P-006	5.8	9.6	1.9
P-007	6.8	10.6	1.9
P-008	7.8	11.6	1.9
P-009	8.8	12.6	1.9
P-010	9.8	13.6	1.9
P-010A	9.8	14.6	2.4
P-011	10.8	15.6	2.4
P-011.2	11	15.8	2.4
P-012	11.8	16.6	2.4
P-012.5	12.3	17.1	2.4
P-014	13.8	18.6	2.4
P-015	14.8	19.6	2.4
P-016	15.8	20.6	2.4
P-017	16.8	21.6	2.4
P-018	17.8	22.6	2.4
P-019	18.8	23.6	2.4
P-020	19.8	24.6	2.4
P-021	20.8	25.6	2.4
P-022	21.8	26.6	2.4
P-022A	21.7	28.7	3.5
P-022.4	22.1	29.1	3.5
P-024	23.7	30.7	3.5
P-025	24.7	31.7	3.5
P-025.5	25.2	32.2	3.5
P-026	25.7	32.7	3.5
P-028	27.7	34.7	3.5
P-029	28.7	35.7	3.5
P-029.5	29.2	36.2	3.5
P-030	29.7	36.7	3.5
P-031	30.7	37.7	3.5
P-031.5	31.2	38.2	3.5
P-032	31.7	38.7	3.5
P-034	33.7	40.7	3.5
P-035	34.7	41.7	3.5
P-035.5	35.2	42.2	3.5
P-036	35.7	42.7	3.5
P-038	37.7	44.7	3.5
P-039	38.7	45.7	3.5
P-040	39.7	46.7	3.5
P-041	40.7	47.7	3.5
P-042	41.7	48.7	3.5
P-044	43.7	50.7	3.5
P-045	44.7	51.7	3.5
P-046	45.7	52.7	3.5
P-048	47.7	54.7	3.5
P-049	48.7	55.7	3.5
P-050	49.7	56.7	3.5
P-047A	46.6	58	5.7
P-048A	47.6	59	5.7
P-050A	49.6	61	5.7
P-052	51.6	63	5.7
P-053	52.6	64	5.7
P-055	54.6	66	5.7
P-056	55.6	67	5.7
P-058	57.6	69	5.7
P-060	59.6	71	5.7

規格	內徑	外徑	厚度
P-062	61.6	73	5.7
P-063	62.6	74	5.7
P-065	64.6	76	5.7
P-067	66.6	78	5.7
P-068	67.6	79	5.7
P-070	69.6	81	5.7
P-071	70.6	82	5.7
P-075	74.6	86	5.7
P-080	79.6	91	5.7
P-085	84.6	96	5.7
P-090	89.6	101	5.7
P-095	94.6	106	5.7
P-100	99.6	111	5.7
P-102	101.6	113	5.7
P-105	104.6	116	5.7
P-110	109.6	121	5.7
P-112	111.6	123	5.7
P-115	114.6	126	5.7
P-120	119.6	131	5.7
P-125	124.6	136	5.7
P-130	129.6	141	5.7
P-132	131.6	143	5.7
P-135	134.6	146	5.7
P-140	139.6	151	5.7
P-145	144.6	156	5.7
P-150	149.6	161	5.7
P-150A	149.5	166.3	8.4
P-155	154.5	171.3	8.4
P-160	159.5	176.3	8.4
P-165	164.5	181.3	8.4
P-170	169.5	186.3	8.4
P-175	174.5	191.3	8.4
P-180	179.5	196.3	8.4
P-185	184.5	201.3	8.4
P-190	189.5	206.3	8.4
P-195	194.5	211.3	8.4
P-200	199.5	216.3	8.4
P-205	204.5	221.3	8.4
P-209	208.5	225.3	8.4
P-210	209.5	226.3	8.4
P-215	214.5	231.3	8.4
P-220	219.5	236.3	8.4
P-225	224.5	241.3	8.4
P-230	229.5	246.3	8.4
P-235	234.5	251.3	8.4
P-240	239.5	256.3	8.4
P-245	244.5	261.3	8.4
P-250	249.5	266.3	8.4
P-255	254.5	271.3	8.4
P-260	259.5	276.3	8.4
P-265	264.5	281.3	8.4
P-270	269.5	286.3	8.4
P-275	274.5	291.3	8.4
P-280	279.5	296.3	8.4
P-285	284.5	301.3	8.4
P-290	289.5	306.3	8.4
P-295	294.5	311.3	8.4
P-300	299.5	316.3	8.4
P-305	304.5	321.3	8.4
P-310	309.5	326.3	8.4

規格	內徑	外徑	厚度
P-315	314.5	331.3	8.4
P-320	319.5	336.3	8.4
P-325	324.5	341.3	8.4
P-330	329.5	346.3	8.4
P-335	334.5	351.3	8.4
P-340	339.5	356.3	8.4
P-345	344.5	361.3	8.4
P-350	349.5	366.3	8.4
P-355	354.5	371.3	8.4
P-360	359.5	376.3	8.4
P-365	364.9	381.3	8.4
P-370	369.5	386.3	8.4
P-375	374.5	391.3	8.4
P-380	379.5	396.3	8.4
P-385	384.5	401.3	8.4
P-390	389.5	406.3	8.4
P-395	394.5	411.3	8.4
P-400	399.5	416.3	8.4
P-405	404.5	421.3	8.4
P-410	409.5	426.3	8.4
P-415	414.5	430.3	8.4
P-420	419.5	436.3	8.4
P-425	424.5	441.3	8.4
P-430	429.5	446.3	8.4
P-435	434.5	451.3	8.4
P-440	439.5	456.3	8.4
P-445	444.5	461.3	8.4
P-450	449.5	466.3	8.4
P-455	454.5	471.3	8.4
P-460	459.5	476.3	8.4
P-465	464.5	481.3	8.4
P-470	469.5	486.3	8.4
P-475	474.5	491.3	8.4
P-480	479.5	496.3	8.4
P-485	484.5	501.3	8.4
P-490	489.5	506.3	8.4
P-495	494.5	511.3	8.4
P-500	499.5	516.3	8.4
P-505	504.5	521.3	8.4
P-510	509.5	526.3	8.4
P-515	514.5	531.3	8.4
P-520	519.5	536.3	8.4
P-525	524.5	541.3	8.4
P-530	529.5	546.3	8.4
P-535	534.5	551.3	8.4
P-540	539.5	556.3	8.4
P-545	544.5	561.3	8.4
P-550	549.5	566.3	8.4
P-555	554.5	571.3	8.4
P-560	559.5	576.3	8.4
P-565	564.5	581.3	8.4
P-570	569.5	586.3	8.4
P-575	574.5	591.3	8.4
P-580	579.5	596.3	8.4
P-585	584.5	601.3	8.4
P-590	589.5	606.3	8.4
P-595	594.5	611.3	8.4
P-600	599.5	616.3	8.4
P-630	629.5	646.3	8.4